

LED-10W/350mA

SPECIFICATIONS

Standards

Converter meets CE standards
 Approved by UL as a class 2 recognized component
 File # E254177

Available Versions

- 901010350-LED 10W-350mA (plastic casing)
- 901010350P-LED 10W-350mA (aluminium casing/European version)
- 901010350PU-LED 10W-350mA (aluminium casing/USA version)

Mechanical and Thermal

PC plastic casing
 Dimensions (mm) 28 x 40 x 100
 Dimensions (in) 1.10" x 1.57" x 3.93"
 Weight 90 grams / 3 ounces
 Tc Max 90°C
 Ta Max 50°C
 Terminal Block Connection
 Aluminium casing/European version
 Dimensions(mm) 27 x 35 x 86
 Weight 165 grams
 Tc Max 90°C
 Ta Max 50°C
 Output wire – 18AWG 200°C
 Input wire – (separate cables) FEP/FEP 0.75mm² 450V 180°C
 Waterproof potting
 Aluminium casing/USA version
 Dimensions (in) 1.06" x 1.37" x 3.38"
 Weight 5.8 ounces
 Tc Max 90°C
 Ta Max 50°C
 Output wire – 18AWG 200°C
 Input wire – UL type 1332 or similar 18 AWG 300V 200°C
 Grounding wire
 Waterproof potting



Electrical

Load	1-10VA
Input	95-265V 0/50/60Hz
Output current	350mA±6%
Output voltage	2-28V
Efficiency	80%
EMC (RFI)	FCC Class B/EN 55015
Harmonics	EN 61000-3-2
Immunity	EN 61547/61047
Safety	EN 61347-2-2
SELV	

Protection and Regulation

Electronic internal resettable short circuit protection. Thermal protection and overload regulation.

